

1 Preparation



1 Unplug cable of battery charger, wind up and place in machine (compartment).




2 Fill solution tank with clean water by using TASKI AquaStop or filling hose.



3 Use TASKI IntelliDose (onboard dilution system) OR dose cleaning product into dosing aid and pour it into the solution tank.




4 Mount squeegee by locking into the squeegee holder.



5 Mount suction hose.




6 Position tool(s) carefully in front - under lifted brush unit.




7 Adjust the seat position and the height of the steering wheel to your individual needs.



8 Turn the machine on by turning key clockwise. Press brush button for coupling tools and press again to lift brush unit.



9 Press program start/stop button to activate last settings of the several aggregates. Switch on the lights




10 Adjust solution flow to your needs by changing water levels.



11 Activate vacuum motor (suction) and ECO mode to lower suction by 50% and hence sound level if needed.




12 Slowly press down the drive pedal. Press slow speed button to lower driving speed by 50%. Press backwards button to change from driving forwards to backwards or vice versa.




13 In case of emergency to immediately stop and shut down the machine. You need to mechanically reset emergency button by turning it clockwise.



14 Press horn button as signal to make notice of your presence.



15 Use the button "offset cleaning" to move the brush deck into offset position. An LED will light up. Press again to position it underneath the machine. The LED switches off.



16 Green lights show the battery level. If a red LED lights up, you have 10 min left to drive the machine to were you charge the batteries.



17 Press program start/stop button to deactivate all aggregates. It saves the last settings of the several aggregates.



18 Turn the machine off by turning key anticlockwise.




19 Drain recovery tank, then drain flexible solution tank, and rinse recovery and solution tank with fresh water.



20 Remove the floating unit from the machine with an anticlockwise rotation, rinse under running and allow to air dry.




21 Take the debris filter out and rinse it under running water and allow to air dry.



22 Remove tools, clean tools and allow to air dry.



23 Remove squeegee and clean it under running water and allow to air dry.



24 Flip dirt filter and store machine with partially open lid (lid rests on dirt filter) for ventilation.



25 Wipe machine with moist cloth and then plug in battery charger cable.

