

<p>1 Preparation</p> <p>Unplug external charger cable.</p>	<p>2</p> <p>Lift seat to open tank cover for tank filling.</p>	<p>3</p> <p>Fill flexible solution tank (bag) with clean water either from water-tap OR with high-speed filling system.</p>	<p>4</p> <p>Use TASKI IntelliDose (on board dilution system) OR dose cleaning product into dosing aid and pour it into the solution tank.</p>	<p>5</p> <p>Mount squeegee: position pockets of the squeegee in front of squeegee holder and push holder down.</p>
<p>6</p> <p>Mount suction hoses: bend hoses to the centre of the machine and plug these in the squeegee.</p>	<p>7</p> <p>Position tool(s) carefully under lifted brush unit.</p>	<p>8</p> <p>Turn the machine on by turning key clockwise. Press brush button for coupling tool(s) and press again to lift brush unit.</p>	<p>9 Operation</p> <p>Press program start/stop button to activate last settings.</p>	
<p>11</p> <p>Activate vacuum motor (suction) and ECO mode to reduce noise level by less suction power.</p>	<p>12</p> <p>Press slow speed button to lower maximum driving speed. Press backwards button to change from driving forwards to backwards or vice versa.</p>	<p>13</p> <p>In case of emergency to immediately stop and shut down the machine. You need to mechanically reset emergency button by turning it clockwise.</p>	<p>14</p> <p>Press horn button to signal your presence.</p>	<p>15</p> <p>Red light indicates either full recovery tank (upper light) or empty solution tank (lower light). In both cases machine stops with normal sequence.</p>
<p>16</p> <p>Green lights show battery level. If a red LED lights up, you have 10 minutes left to drive machine somewhere you can charge batteries.</p>	<p>17</p> <p>Slowly press down the drive pedal and clean the floor.</p>	<p>18</p> <p>Press program start/stop button to deactivate all aggregates. It saves the last settings of several aggregates.</p>	<p>19</p> <p>Turn the machine off by turning key anticlockwise.</p>	<p>20 Maintenance</p> <p>Drain recovery tank, then drain flexible solution tank, rinse recovery and solution tank with fresh water.</p>
<p>21</p> <p>Remove filter sieve from water pump and clean under running water.</p>	<p>22</p> <p>Take the dirt filter out. Remove the floating unit (filter and floater) with an anticlockwise rotation.</p>	<p>23</p> <p>Clean dirt filter and floating unit under running water and allow to air dry.</p>	<p>24</p> <p>Remove tools, clean and allow to air dry.</p>	<p>25</p> <p>Remove squeegee.</p>
<p>26</p> <p>Clean squeegee under running water and allow to air dry.</p>	<p>27</p> <p>Wipe machine with moist cloth.</p>	<p>28</p> <p>Flip dirt filter and store machine with partially open lid (lid rests on dirt filter) for ventilation.</p>	<p>29</p> <p>Place drain hose, suction hoses and the squeegee in their holders to store the machine.</p>	<p>30</p> <p>Plug in external charger cable.</p>

